



Stacked ALL-IN-ONE ESS



**5.5kw+5-30k
wh**

Contact Information

+254 735 449 449

📍 Address
Penta Mabati Business Center,
1st Floor, Ruiru Kamiti Road

☎ +254 735 449 449
🌐 www.dipower.co.ke

1.Scope of application

This product is a 51V stacked all-in-one home energy storage system, which is floor-standing. It can supply power to household TV, computer, air conditioner, lighting lamp, etc. It can also be used as an uninterruptible power supply. It is suitable for off-grid energy storage system and outputs AC power with stable frequency and constant voltage. During normal operation, it provides singlephase AC power; In case of failure, the battery pack will provide rated power supply to the inverter without interruption.

2.The main features of the product are as follows:

1. Easy installation, easy to move, stable and firm structure;
2. Stackable energy storage LFP battery, maximum capacity 30kwh;
3. Integrated 5kw power high-frequency inverter, 120-450V wide range MPPT
4. All-in-one integrated system, power supply can be used immediately after startup
5. Intelligent communication management chip, efficient, stable and safe power supply system
6. Global cloud platform & mobile APP access

3.ALL-IN-ONE ESS Specifications

General Technical Characteristics						
General specification						
Model	DDYTJ51100-5.5K	DDYTJ51200-5.5K	DDYTJ51300-5.5K	DDYTJ51400-5.5K	DDYTJ51500-5.5K	DDYTJ51600-5.5K
The layer number	Layer 1	Layer 2	Layer 3	Layer 4	Layer 5	Layer 6
Capacity	5.12kWh	10.24kWh	15.36kWh	20.48kWh	25.6kwh	30.72kwh
Size (L*W*H)	680*400*430mm	680*400*592mm	680*400*754mm	680*400*916mm	680*400*1078mm	680*400*1240mm
Weight	80KG	130KG	180KG	230KG	280KG	330KG
Storage temperature	-20°C ~ 45°C					
Relative humidity	5% ~ 95%					
Operating temperature	-10°C ~ 55°C					
Class of protection	IP21 (Indoor)					
Topology structure	Natural convection and fan cooling					
Display	LCD					
Communication interface	USB/RS485/WIFI					
Installation Mode	Floor/mobile					
Max. efficiency (battery)	94%					
Max. efficiency (PV)	97%					
Max. efficiency (AC)	95%					

Protection Function	Short circuit protection, overload protection, AC leakage protection, ground fault protection, surge protection, DC polarity protection
Battery pack Specifications	
Rated battery voltage	51.2V
Battery voltage range	40-60V
Max. discharge current	100A
Max. charging current	100A
Capacity of energy	5.12KWh
Battery Type	Lithium iron phosphate (LiFePO4)
Life of cycle	6000 times (25°C, 0.3C, 80%DOD, > 60%C25°C)
Operating voltage	44.8-57.6V
Internal impedance	≤ 20 mΩ
Operating temperature	-20°C ~ 40°C (charging temperature) / -40°C ~ 45°C (discharging temperature)
Storage temperature	-20°C ~ 45°C
Storage humidity	5% ~ 95%
Module connection	Maximum 6 batteries in parallel (5.12 KWH per module)
Monitoring parameters	System voltage, current, battery voltage
Communication interface	CAN/RS485
Weight	50KG
Size (L*W*H)	680*400*192mm
Class of protection	IP21 (Indoor)
The quality assurance	5 years
Security Certification	IEC62619、IEC61000、UN38.3
Inverter Specifications	
Rated output voltage	230Vac

Ac input voltage	220/230Vac	
Rated output power	5500VA	
Ac output power	5500W	
Ac output frequency	50/60Hz	
Ac Max. charging current	16A	
Max. PV input current	50A	
Max. PV input power	5500W	
Max. PV charging current	80A	
PV voltage range	120V-500Vdc	
MPPT voltage range	120V-450Vdc	
Ac input frequency	50/60Hz (Automatic detection)	
Conversion time (invert)	10ms	
Operating temperature	-15°C ~ 55°C	
Storage temperature	-25°C ~ 60°C	
Storage humidity	5% ~ 95%	
Weight	30KG	
Size (L*W*H)	680*400*177mm	
Class of protection	IP21 (Indoor)	
The quality assurance	5 years	
EMC Certification Level	EN61000	
Certification	CE (IEC 62619-1)	
Battery carton packaging size (L*W*H)		About 770+-mm*490+-mm*277+-mm
Inverter carton packaging size (L*W*H)		About 770+-mm*490+-mm*260+-mm

Base carton packaging size (L*W*H)	About 770+-mm*490+-mm*220+-mm
Parts List	AC mains input connector 1 PCS; Wifi Module 1PCS; Desiccant 3 BAG; Use Manual 1 PCS; EU Plug 1PCS; PV input connector 1PCS